


DOUBLE EAR HOSE CLAMPS



A top quality clamp, offers you a tight seal of the water line coupling onto the hose. The double-ear design will not damage the hose – unlike low cost, screw-type clamps.

- **Stainless Steel**
- **Provides tight, positive closure**
- **Zinc Plated Available. . . Inquire**

EASY TO INSTALL

- 1.) Slip onto hose.
Close one side all the way.
- 2.) Close the opposite side.

The first ear will slightly open. Do not close it. This will add strength to clamp to give a spring-like action to hold against pressure.

- NOTE -

When ordering, select Nominal Size nearest to, but always larger than O.D. of hose to be clamped after insert has been fitted.

PART #	Nominal I.D.	Actual I.D.		Width	Thickness	Inner width of ear	PRICE each
		closed	open				
0041R	5/32	.122	.161	.138	.0197	.0591	\$.22
0045R	11/64	.138	.177	.138	.0236	.0591	\$.22
0305R	3/16	.116	.197	.19	.0276	.0980	\$.22
0507R	1/4	.197	.276	.23	.0276	.118	\$.23
0709R	5/16	.27	.354	.276	.0394	.126	\$.23
0811R	3/8	.315	.433	.276	.0394	.177	\$.23
0911R	7/16	.354	.433	.276	.0394	.138	\$.25
1113R	1/2	.433	.512	.276	.0394	.138	\$.25
1315R	9/16	.512	.591	.295	.0394	.158	\$.25
1517	19/32	.59	.669	.315	.0473	.197	\$.25
1518	5/8	.591	.708	.315	.0473	.197	\$.33
1720	3/4	.669	.787	.335	.0473	.236	\$.36
1922	13/16	.748	.866	.354	.0591	.256	\$.64
2023	7/8	.787	.905	.354	.0591	.256	\$.41
2225	15/16	.866	.984	.394	.0591	.256	\$.76
2327	1	.905	1.063	.394	.0591	.276	\$.38
2528	1-1/16	.984	1.102	.394	.0591	.256	\$.40
2731	1-1/8	1.063	1.22	.394	.0591	.295	\$.57
2831	1-3/16	1.102	1.22	.394	.0591	.256	\$.41
3134	1-5/16	1.22	1.339	.394	.0591	.295	\$.44
3437	1-7/16	1.339	1.457	.394	.0591	.315	\$.59
3740	1-1/2	1.457	1.575	.394	.0591	.315	\$ 1.02
4043	1-5/8	1.575	1.693	.394	.0591	.335	\$.49
4346	1-3/4	1.693	1.811	.394	.0591	.335	\$.50



CLAMP PINCHERS

Part #1098

\$29.00

© 2014 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: molders@molderschoice.com