

MOLDERS CHOICE NOZZLE REFERENCE GUIDE

We don't repeat pages and show every possible nozzle for all machine manufacturers.

Simply tell us your machine, size, and thread specification...we'll do the rest

CALL US FIRST FOR YOUR NOZZLE NEEDS!

Press Thread	Rear Opening	Thread Length
ARBURG		
24 mm - 1.5mm LH	8 mm	1.13
24 mm - 1.5mm RH	8 mm	1.13
35 mm - 2 mm RH	19 mm	1.06
35 mm - 2 mm LH	19 mm	1.06
39 mm - 2 mm RH	19 mm	1.19
39 mm - 2 mm LH	30 mm	1.19
45 mm - 1.5 mm LH	22 mm	1.19
45 mm - 1.5 mm LH	22 mm	1.38
45 mm - 1.5 mm LH	25 mm	1.19
45 mm - 1.5 mm LH	25 mm	1.38
45 mm - 2 mm LH	18 mm	1.19
45 mm - 2 mm LH	18 mm	1.38
45 mm - 2 mm LH	18 mm	1.50
45 mm - 2 mm LH	22 mm	1.19
45 mm - 2 mm LH	22 mm	1.38
45 mm - 2 mm LH	22 mm	1.50
45 mm - 2 mm LH	25 mm	1.19
45 mm - 2 mm LH	25 mm	1.38
45 mm - 2 mm LH	25 mm	1.50
45 mm - 2 mm LH	25 mm	1.19
50 mm - 2 mm RH	30 mm	1.38
50 mm - 2 mm LH	30 mm	1.38
52 mm - 2 mm RH	30 mm	1.25
52 mm - 2 mm LH	30 mm	1.25
52 mm - 2 mm RH	35 mm	1.25
52 mm - 2 mm LH	35 mm	1.25
52 mm - 2 mm RH	40 mm	1.25
52 mm - 2 mm LH	40 mm	1.25
55 mm - 2 mm LH	40 mm	1.44
60 mm - 2 mm LH	30 mm	1.00

Press Thread	Rear Opening	Thread Length
AUTOJECTOR		
1-1/2" - 12	1.00	.75
1-3/4" - 12	.78	.88
1-3/4" - 12	1.25	.88
2 " - 12	1.50	.91
BATTENFELD		
35 mm - 2 mm	.812	1.19
35 mm - 2 mm	25 mm	1.13
35 mm - 2 mm	21 mm	.98
35 mm - 2 mm	.375	1.19
35 mm - 2 mm	30 mm	1.25
35 mm - 2 mm	19 mm	.91
35 mm - 2 mm	22 mm	1.00
35 mm - 2 mm	1.00	1.25
40 mm - 2 mm	25 mm	.94
40 mm - 2 mm	30 mm	.94
40 mm - 2 mm	20 mm	1.97
40 mm - 2 mm	.812	1.00
40 mm - 2 mm	1.00	1.50
45 mm - 2 mm	35 mm	1.19
55 mm - 3 mm	33 mm	1.50
55 mm - 3 mm	32 mm	1.56
65 mm - 3 mm TRAP*	48 mm	1.75
65 mm - 3 mm	50 mm	2.00
65 mm - 3 mm	2.00	2.00
90 mm - 4 mm TRAP*	48 mm	2.36
BOY		
24 mm - 1.5 mm	13 mm	1.08
24 mm - 1.5 mm	14 mm	1.08
24 mm - 1.5 mm	16 mm	1.08

(continued next page)

© 2009 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: molders@molderschoice.com

MOLDERS CHOICE NOZZLE REFERENCE GUIDE

CALL US FIRST FOR YOUR NOZZLE NEEDS!

Press Thread	Rear Opening	Thread Length
BOY (continued)		
33 mm - 1.5 mm	22 mm	.88
33 mm - 1.5 mm	24 mm	.88
35 mm - 1.5 mm	16 mm	1.42
35 mm - 1.5 mm	25 mm	1.42
CINCINNATI		
1-1/4" - 12	.750	.83
1-1/2" - 12	.500	2.00
1-1/2" - 12	.750	2.00
1-3/4" - 8	.750	1.75
1-3/4" - 8	1.000	1.63
2" - 8	1.000	1.88
2" - 16	1.000	1.88
2-3/4" - 6	1.75	1.75
DEMAG (also see Van Dorn)		
30 mm - 2 mm	20 mm	30 mm
45 mm - 3 mm	25 mm	
60 mm - 3 mm	25 mm	36 mm
60 mm - 3 mm	40 mm	40 mm
60 mm - 2 mm	30 mm	45 mm
ENGEL		
7/8" - 14	.490	.88
28 mm - 1.5 mm	.472	1.26
40 mm - 3 mm	1.25	1.15
40 mm - 2 mm	25 mm	1.18
45 mm - 1.5 mm	30 mm	1.06
EGAN		
1-1/8" - 12	.562	1.25
1-1/8" - 12	.625	1.38
1-1/8" - 12	.750	1.38
1-5/8" - 8	.750	1.50
1-3/4" - 8	.750	1.75
2-1/4" - 8	.750	1.50

Press Thread	Rear Opening	Thread Length
HAITIAN		
39mm - 2 mm	24 mm	
45mm - 4 mm	20 mm	
HPM		
1-5/8" - 12 (Female)	.750	.63
1-5/8" - 12 (Female)	.500	.63
1-1/4" - 8 (Buttress)	.625	1.34
1-3/4" - 8	.750	1.75
2-1/2" - 8	1.000	1.50
3-1/8" - 8	1.000	1.43
3-1/8" - 8 (5/8" Ext. Seat)	1.000	2.18
HUSKY		
1-3/4" - 8	.375	1.63
1-3/4" - 8	1.000	1.63
45 mm - 3 mm	16 mm	2.06
64 mm - 4 mm	22 mm	2.36
JACO		
7/8" - 14	.500	.88
JSW		
45 mm - 3 mm	25 mm	1.63
50 mm - 3 mm	15 mm	2.25
55 mm - 3 mm	8 mm	1.58
KAWAGUCHI		
1" - 12	.625	1.09
1-3/4" - 8	.937	1.75
1-3/4" - 8	1.250	1.75
1-1/4" - 12	7/8"	1.63
30 mm - 1.5 mm	12 mm	1.13
30 mm - 3 mm	.500	1.88

(continued next page)

© 2009 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: molders@molderschoice.com

MOLDERS CHOICE NOZZLE REFERENCE GUIDE

CALL US FIRST FOR YOUR NOZZLE NEEDS!

Press Thread	Rear Opening	Thread Length
KAWAGUCHI (continued)		
30 mm - 3.5 mm	12 mm	1.63
38 mm - 3 mm	14 mm	1.63
45 mm - 3 mm	16 mm	1.50
55 mm - 3 mm	.750	1.94
KLOCKNER FERROMATIK		
1" BPT	.394	1.41
30 mm - 2 mm	.394	.78
30 mm - 1.5 mm	.315	.63
52 mm - 3 mm	.63	3.03
KRAUSS-MAFFEI		
1-1/4' - 12	.750	1.38
1-3/4" - 8	.750	1.63
12 mm - 1 mm (Female)	5 mm	.55
45 mm - 2 mm	19 mm	1.63
55 mm - 3 mm	36 mm	1.31
70 mm - 4 mm TRAP	35 mm	1.71
85 mm - 2 mm	55 mm	1.57
110 mm - 3 mm	70 mm	2.66
MEIKI		
22 mm - 1.5 mm	.610	1.00
38 mm - 11 T.P.I.	.890	1.13
METAL MAC		
45 mm - 2 mm	1.360	1.50
48 mm - 2 mm	40 mm	
52 mm - 2 mm	45 mm	2.36
55 mm - 2 mm	45 mm	2.36
58 mm - 2 mm	50 mm	2.20
70 mm - 3 mm	54 mm	2.55
80 mm - 3 mm	65 mm	2.60

Press Thread	Rear Opening	Thread Length
MIR		
75 mm - 3 mm	1.78	2.07
80 mm - 3 mm	1.97	2.48
MITSUBISHI		
1-1/2" - 12	.92	.98
1-1/2" - 12	.59	1.38
1-1/2" - 12	.750	1.38
NATCO		
2-1/4" - 8 (Female)	.600	1.07
2-1/4" - 8 (Female)	.750	1.07
3' - 8	1.750	1.31
NEGRI-BOSSI		
2" - 8	.750	2.13
33 mm - 1.5 mm	19 mm	.75
40 mm - 2 mm	28 mm	.94
52 mm - 2.5 mm	28 mm	1.52
58 mm - 2 mm	38 mm	1.77
58 mm - 3 mm	45 mm	1.49
64 mm - 3 mm	34 mm	1.50
64 mm - 4 mm	1.245	2.34
70 mm - 2 mm	45 mm	2.39
70 mm - 3 mm	45 mm	1.57
72 mm - 3 mm	60 mm	1.88
82 mm - 3 mm	2.77	2.25

(continued next page)



© 2009 MOLDERS CHOICE, Inc.

24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: molders@molderschoice.com

MOLDERS CHOICE NOZZLE REFERENCE GUIDE

CALL US FIRST FOR YOUR NOZZLE NEEDS!

Press Thread	Rear Opening	Thread Length
NEW BRITAIN		
4" - 6 (Female)	55 mm	3.20
44 mm - 3 mm TRAP*	30 mm	1.44
45 mm - 4 mm	12 mm	1.88
55 mm - 3 mm	.750	1.56
55 mm - 3 mm	1.26	1.56
65 mm - 3 mm TRAP*	48 mm	2.00
NIIGATA		
40 mm - 3 mm	30 mm	1.25
50 mm - 2 mm	1.35	2.02
NISSEI		
35 mm - 2 mm	20 mm	1.00
35 mm - 2 mm	20 mm	1.44
40 mm - 2 mm	20 mm	1.31
40 mm - 2 mm	20 mm	1.63
45 mm - 2 mm	1.195	1.19
50 mm - 2 mm	26 mm	1.70
50 mm - 12 T.P.I.		1.85
60 mm - 2 mm	47 mm	1.87
60 mm - 3 mm	1.000	1.50
1-3/8" - 12	.750	1.63
NEWBURY		
1-1/2" - 12	.843	1.19
REED		
1-1/4" - 8 (Buttress)	.625	1.31
1-1/2" - 12	.812	1.66
1-3/4" - 8	.750	1.75
1-3/4" - 12	.1000	1.00
2" - 12 (Female)	1.250	1.25

Press Thread	Rear Opening	Thread Length
SANDRETTO		
40 mm - 3 mm	30 mm	40 mm
50 mm - 3 mm	35 mm	55 mm
55 mm - 3 mm	40 mm	55 mm
60 mm - 3 mm	45 mm	60 mm
70 mm - 4 mm	55 mm	64 mm
SUMITOMO		
48 mm - 2 mm	32 mm	1.31
TOSHIBA		
1-1/2" - 12	15 mm	1.38
1-1/2" - 12	15 mm	1.00
3-1/4" - 8	52 mm	1.97
38 mm - 1.5 mm	15 mm	.96
48 mm - 1.5 mm	25 mm	1.62
60 mm - 4 mm	28 mm	1.62
60 mm - 4 mm	32 mm	1.61
60 mm - 4 mm	36 mm	1.62
80 mm - 4 mm	55 mm	2.94
TOYO		
36 mm - 2 mm	23 mm	1.30
42 mm - 3 mm	24 mm	1.26
50 mm - 3 mm	26 mm	2.06
65 mm - 4 mm	32 mm	1.61
65 mm - 4mm	40 mm	1.61
TRUEBLOOD		
7/8" - 12	.246	.78
1-1/4" - 12	.63	1.16
UBE		
50 mm - 2 mm	35 mm	1.42
VAN DORN (also see Demag)		
1-1/4" - 12	.750	1.63
1-3/4" - 8	1.25	1.75

© 2009 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: molders@molderschoice.com