

# Standard WATERLINE HOSE

**Works with standard hose clamps.  
Color Coordinate your hose hookups.**

Progressive molders realize that time is money! Any action to reduce mold setup time and ensure proper hose hookup means your setup personnel are working to greater efficiency. When cooling your mold with chiller or cooling tower water, use BLUE or BLACK hose TO the mold ports. Use the RED hose as your RETURN lines FROM the mold returning to your chiller etc.

## ADVANTAGES:

- Economical
  - Abrasion, age and weather resistant
  - -40° F to 180° F temperature range
  - EPDM cover and tube
  - 2 to 4 Textile spirals for reinforcement
  - Color: Red, Black & Blue
  - **UL- Ultra-Force** Hose is best used for chiller water
- Temperature range: -20° F to 150° F  
Cover: Rubber Modified, non marking thermoplastic / Pin pricked



See Pages 269 and 270  
for Hose Clamps

## PRICES

PART#	Hose I.D.	Hose O.D.	Color	Working Pressure	Price Per Foot	PART#	Hose I.D.	Hose O.D.	Color	Working Pressure	Price Per Foot
SWH14R	1/4"	19/32"	Red	250 psi	<b>\$.48</b>	SWH34BK	3/4"	1-3/16"	Black	250 psi	<b>\$1.25</b>
SWH14BK	1/4"	19/32"	Black	250 psi	<b>\$.48</b>	SWH100R	1"	1-1/2"	Red	250 psi	<b>\$1.80</b>
SWH38R	3/8"	23/32"	Red	250 psi	<b>\$.67</b>	SWH100BK	1"	1-1/2"	Black	250 psi	<b>\$1.80</b>
SWH38BK	3/8"	23/32"	Black	250 psi	<b>\$.67</b>	SWH114R	1-1/4"	1-25/32"	Red	250 psi	<b>\$3.50</b>
SWH12R	1/2"	7/8"	Red	250 psi	<b>\$.80</b>	SWH114BK	1-1/4"	1-25/32"	Black	250 psi	<b>\$3.50</b>
SWH12BK	1/2"	7/8"	Black	250 psi	<b>\$.80</b>	SWH112R	1-1/2"	1-31/32"	Red	250 psi	<b>\$4.25</b>
SWH58R	5/8"	31/32"	Red	250 psi	<b>\$.95</b>	SWH112BK	1-1/2"	1-31/32"	Black	250 psi	<b>\$4.25</b>
SWH58BK	5/8"	31/32"	Black	250 psi	<b>\$.95</b>	SWH200R	2"	2-23/32"	Red	250 psi	<b>\$9.00</b>
SWH34R	3/4"	1-3/16"	Red	250 psi	<b>\$1.25</b>	SWH200BK	2"	2-23/32"	Black	250 psi	<b>\$9.00</b>

© 2009 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

**1-800-809-4623**

WebSite: [www.molderschoice.com](http://www.molderschoice.com) • Email: [molders@molderschoice.com](mailto:molders@molderschoice.com)