

# SAFETY DATA SHEET.

Issuing date 29-Sep-2016

Revision Date 05-Mar-2018

Version 2

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product name** Bulk RP1624,1601,1605, 1655 Rust Preventive

### Recommended use of the chemical and restrictions on use

**Product code** F01720

**Product Type** Highly Flammable Liquid and Vapor  
**Synonyms** None

### Supplier's details

**Recommended Use** Protective Coating against rust and corrosion.  
**Uses advised against** No information available

**Manufactured For:**  
Molders Choice Inc.  
5380 Naiman Parkway Suite E  
Solon, OH 44139  
Phone: (800) 809-4623

**Manufacturer**  
American Jetway Corporation  
34136 Myrtle Street  
Wayne, MI 48184-0126  
AMERICAN JETWAY 1-734-721-5930

**Emergency telephone number**  
**Chemical Emergency Phone Number**

CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

## 2. HAZARDS IDENTIFICATION

### Classification

Acute Toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Harmful if swallowed  
 Causes serious eye irritation  
 Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness.  
 Causes damage to organs (Central Nervous System, Eyes, Kidney, Liver, Respiratory System, and Skin) through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways  
 Highly flammable liquid and vapor



**Appearance** Clear

**Physical state** Liquid

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces.-No smoking.  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

#### Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED : Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a poison center/doctor  
Do NOT induce vomiting.  
Rinse mouth  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed.  
Keep cool.

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None

**Other information**

0% of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PETROLEUM DISTILLATES	64742-47-8	25-35
HEPTANE	64742-49-0	10-20
METHYLCYCLOHEXANE	108-87-2	1-10
TOLUENE	108-88-3	1-10
N-OCTANE	111-65-9	1-10
PETROLEUM DISTILLATES	8052-41-3	1-10
2-BUTOXYETHANOL	111-76-2	1-10
ETHYLENE GLYCOL	107-21-1	<0.1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures for different exposure routes**

<b>General advice</b>	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
<b>Eye contact</b>	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
<b>Skin contact</b>	If on skin (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Call a physician or Poison Control Center immediately. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Most important symptoms/effects, acute and delayed**

**Main Symptoms** Harmful if swallowed. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause respiratory irritation or cause drowsiness and dizziness. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Water fog. Dry chemical. Foam. Carbon dioxide (CO<sub>2</sub>). Cool containers/tanks with water spray. Water fog. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Cool containers / tanks with water spray.

**Unsuitable Extinguishing Media** . Do not smoke. Cool containers / tanks with water spray. Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Flammable. In the event of fire, cool tanks with water spray. Keep containers and surrounding areas cool with water spray. Keep product and empty container away from heat and sources of ignition. Extremely Flammable / Flammable.

**Hazardous Combustion Products** Carbon oxides , Hydrocarbons, Fumes. Chlorine gas. Halogenated compounds.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions**

**Environmental precautions** Vapors can accumulate in low areas. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods for cleaning up** Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

**Conditions for safe storage, including any incompatibilities**

**Technical measures/Storage conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up. Keep cool.

**Incompatible products** Strong acids, alkalis, oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HEPTANE 64742-49-0	TLV: 400 ppm STEL: 500 ppm	TWA: 500 ppm	-
METHYLCYCLOHEXANE 108-87-2	TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup>	IDLH: 1200 ppm TWA: 400 ppm TWA: 1600 mg/m <sup>3</sup>
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
N-OCTANE 111-65-9	TWA: 300 ppm	TWA: 500 ppm TWA: 2350 mg/m <sup>3</sup> (vacated) TWA: 300 ppm (vacated) TWA: 1450 mg/m <sup>3</sup> (vacated) STEL: 375 ppm (vacated) STEL: 1800 mg/m <sup>3</sup>	IDLH: 1000 ppm Ceiling: 385 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 75 ppm TWA: 350 mg/m <sup>3</sup>
PETROLEUM DISTILLATES 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>
ETHYLENE GLYCOL 107-21-1	Ceiling: 100 mg/m <sup>3</sup> aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m <sup>3</sup>	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Safety glasses with side-shields.
<b>Skin and body protection</b>	Chemical resistant apron. Protective gloves.
<b>Respiratory protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>Hygiene measures</b>	Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and chemical properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Solvent
<b>Appearance</b>	Clear	<b>Odor Threshold</b>	
<b>Color</b>	Dark Amber		
<b>Property</b>	<b>Values</b>	<b>Remarks • Methods</b>	
<b>pH</b>	No information available		
<b>Melting/freezing point</b>	No information available		
<b>Boiling point/boiling range</b>			
<b>Flash Point</b>	-6 °C / 21 °F	Based on lowest flashpoint of the products constituents.	
<b>Evaporation rate</b>	No information available		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limits in Air</b>			
<b>upper flammability limit</b>			
<b>lower flammability limit</b>			
<b>Vapor pressure</b>			
<b>Vapor density</b>			
<b>Specific Gravity</b>	0.787		
<b>Water solubility</b>	No information available		
<b>Partition coefficient: n-octanol/water</b>			
<b>Autoignition temperature</b>	No information available		
<b>Decomposition temperature</b>			
<b>Viscosity</b>	No information available		
<b>Explosive properties</b>			
<b><u>Other information</u></b>			
<b>VOC Content(%)</b>	69.28		

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to Avoid

Extremes of temperature and direct sunlight.

### Incompatible Materials

Strong acids, alkalis, oxidizing agents.

**Hazardous Decomposition Products**

Carbon oxides , Hydrocarbons, Fumes.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	May cause respiratory irritation. May cause drowsiness or dizziness.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Skin irritation may occur if person excessively exposes product to the skin.
<b>Ingestion</b>	Harmful if swallowed. May be fatal if swallowed and enters airways.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
HEPTANE 64742-49-0	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 73680 ppm ( Rat ) 4 h
METHYLCYCLOHEXANE 108-87-2	> 3200 mg/kg ( Rat )	> 86700 mg/kg ( Rabbit )	-
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
N-OCTANE 111-65-9	-	-	= 118 g/m <sup>3</sup> ( Rat ) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h
ETHYLENE GLYCOL 107-21-1	= 4700 mg/kg ( Rat )	= 10600 mg/kg ( Rat )	-

**Information on toxicological effects**

<b>Symptoms</b>	Harmful if swallowed. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to organs (Listed Below) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
-----------------	---

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	Under normal conditions there is no skin irritation. Excessive exposure of product with skin may cause skin irritation.
<b>Eye damage/irritation</b>	Irritating to eyes.
<b>Sensitization</b>	Not a known sensitizer.
<b>Germ Cell Mutagenicity</b>	Not a germ cell mutagen.
<b>Carcinogenicity</b>	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-
2-BUTOXYETHANOL 111-76-2	-	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

<b>Reproductive toxicity</b>	Product is or contains a chemical which is a known or suspected reproductive hazard.
<b>Specific target organ systemic toxicity (single exposure)</b>	May cause drowsiness and dizziness. May cause drowsiness and dizziness.

<b>Specific target organ systemic toxicity (repeated exposure)</b> <b>Chronic toxicity</b>	Causes damage to Target Organs listed below through prolonged or repeated exposure.
<b>Target Organ Effects</b> <b>Aspiration hazard</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Eyes, Skin, Liver, Kidneys, Respiratory System, Central Nervous System. May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	1853 mg/kg
<b>ATEmix (dermal)</b>	3521 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	37 mg/l
<b>ATEmix (inhalation-vapor)</b>	76 mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54 mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
N-OCTANE 111-65-9	-	-	-	0.38 mg/L EC50 water flea 48h
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h
ETHYLENE GLYCOL 107-21-1	6500 - 13000 mg/L EC50 Pseudokirchneriella subcapitata 96h	41000 mg/L LC50 Oncorhynchus mykiss 96h 14 - 18 mg/L LC50 Oncorhynchus mykiss 96h static 27540 mg/L LC50 Lepomis macrochirus 96h static 40761 mg/L LC50 Oncorhynchus mykiss 96h static 40000 - 60000 mg/L LC50 Pimephales promelas 96h static 16000 mg/L LC50 Poecilia reticulata 96h static	-	46300 mg/L EC50 Daphnia magna 48h



**Persistence and degradability****Bioaccumulation**

Chemical Name	log Pow
TOLUENE 108-88-3	2.7
N-OCTANE 111-65-9	5.18
2-BUTOXYETHANOL 111-76-2	0.81
ETHYLENE GLYCOL 107-21-1	-1.93

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment**

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, HEPTANE ),3, PG II

**IATA** UN1993, FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES , HEPTANE), 3, PGII

**IMDG** UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, HEPTANE),3, PG II

### 15. REGULATORY INFORMATION

**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	X	X	X	x	X	X	X	X
HEPTANE	X	X	X	Not listed	X	X	X	X
METHYLCYCLOHEXANE	X	X	X	X	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
N-OCTANE	X	X	X	X	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	X	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X

ETHYLENE GLYCOL	X	X	X	X	X	X	X	X
-----------------	---	---	---	---	---	---	---	---

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	6.46	1.0
2-BUTOXYETHANOL - 111-76-2	111-76-2	3.96	1.0
ETHYLENE GLYCOL - 107-21-1	107-21-1	<0.1	1.0

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Star Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**Clean Water Act**

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X

**CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
ETHYLENE GLYCOL 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemical Name	California Prop. 65
TOLUENE - 108-88-3	Developmental 1-10%
ETHYLENE GLYCOL - 107-21-1	Developmental <0.1%

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYLCYCLOHEXANE 108-87-2	X	X	X
TOLUENE 108-88-3	X	X	X
N-OCTANE 111-65-9	X	X	X
PETROLEUM DISTILLATES 8052-41-3	X	X	X
2-BUTOXYETHANOL 111-76-2	X	X	X
ETHYLENE GLYCOL 107-21-1	X	X	X

EPA Pesticide Registration Number Not applicable

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

#### WHMIS Hazard Class

B2 Flammable liquid

D2B Toxic materials

### 16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 3	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 3	Physical Hazard 0	Personal protection B
<i>Chronic Hazard Star Legend</i>		<i>Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system damage</i>		

#### Prepared By

American Jetway  
34136 Myrtle Street  
Wayne, MI 48184  
Tel.734-721-5930

#### Issuing date

29-Sep-2016

#### Revision Date

05-Mar-2018

#### Revision Note

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**